



GENERATOR MODELS:
WQ32-ENCL 32kW/40kVA @ 60Hz
WQ40-ENCL 40kW/50kVA @ 60Hz
(Also available in 50Hz)



Rear Access Panel includes:

- Engine control panel
- AC distribution panel
- Volt and Hertz meter package
- Idle/rated speed control

MODELS AVAILABLE:
WQ30-ENCL 32kW and WQ40-ENCL 40kW

GENERATOR SET SPECIFICATIONS AND STANDARD FEATURES

- Yanmar Liquid cooled diesel engine
- Newage-Stamford single bearing, brushless generator *CSA/UL Approved*
- 12ga All-Weather powder coated metal enclosure with lockable doors
- 80 Imp. Gal (380L) internal fuel tank with fuel gauge
- Low oil pressure, high coolant temperature automatic safety shutdown system
- Key start panel with DC volt meter, hour meter, oil pressure, coolant temperature gauges and volt/hertz meter package
- Lifting hook and tie down pockets
- Residential grade exhaust muffler system
- CSA approved AC Distribution panel
- G24 Standard battery and box
- Electronic governor speed control

Available Options

- Remote oil drain
- Remote fuel tank valves for easy connection with auxiliary tank
- Customized AC distribution panel
- Engine coolant heater
- Positive air shutoff valve
- Single or tandem axle trailer
- Enclosure Winter front

GENERATOR SETS POWERED BY
YANMAR



Optional trailer and custom AC Distribution packages available. Units provide excellent access for serviceability. Large 380L fuel tank for extended runtime.

GENERATOR SET SPECIFICATIONS:

WQ30-ENCL

Output 3 phase 60Hz: 32kW/40kVA (continuous) / 35kW/44kVA (intermittent)

Output 1 phase 60Hz: 32kW/32kVA (continuous) / 35kW/35kVA (intermittent)

Voltage Available: 120/240V 1Ph; 120/208V 3Ph; 480V 3Ph; 600V 3Ph

Engine: Yanmar 4TNV98; 4 cylinder; 3.3L; 1800 RPM; EPA iTier 4

Generator: Newage-Stamford single bearing , brushless

Dimensions: 78”L x 35”W x 56”H; 1981mm L x 889mm W x 1422mm H

Weight: 2275lb/1030kg (dry) 2970lb/1347kg (wet)

Fuel Consumption (50%/100% load): 5.5lph/10.0lph

Fuel Tank Capacity: 90 US Gal (340L)

WQ40-ENCL

Output 3 phase 60Hz: 40kW/50kVA (continuous) / 45kW/56kVA (intermittent)

Output 1 phase 60Hz: 40kW/40kVA (continuous) / 45kW/45kVA (intermittent)

Voltage Available: 120/240V 1Ph; 120/208V 3Ph; 480V 3Ph; 600V 3Ph

Engine: Yanmar 4TNV98T; 4 cylinder; Turbo charged; 3.3L; 1800 RPM; EPA Tier 3

Generator: Newage-Stamford single bearing , brushless

Dimensions: 78”L x 35”W x 56”H; 1981mm L x 889mm W x 1422mm H

Weight: 2450lb/1110kg (dry) 3145lb/1427kg (wet)

Fuel Consumption (50%/100% load): 6.7lph/12.2lph

Fuel Tank Capacity: 90 US Gal (340L)