



### WQ60 Diesel Generator Set

**Prime output 60Hz:** 60kW / 75kVA  
**Standby output 60Hz:** 65kW / 80kVA

**Prime output 50Hz:** 50kW / 62kVA  
**Standby output 50Hz:** 55kW / 70kVA

**Fuel Consumption L/hr:**  
 1/4 load: 4.8                      1/2 load: 8.1  
 3/4 load: 11.9                     Full load: 15.4

Generator set pictured may include optional accessories.

Voltage	Frequency	P.F.	Amps	kW	kVA
120/240 - 1PH	60Hz	1.0	235	56	56
120/208 - 3PH	60Hz	0.8	208	60	75
277/480 - 3PH	60Hz	0.8	90	60	75
347/600 - 3PH	60Hz	0.8	72	60	75

#### GENERATOR SET FEATURES:

- Isuzu liquid cooled diesel engine
- Newage-Stamford generator with Automatic Voltage Regulator -*CSA/UL approved*
- Low oil pressure and high water temperature Safety Shutdown System
- Digital generator control panel with LED display (DC volt meter, hour meter, oil pressure, coolant temperature gauges, AC Volt and Frequency)
- Standard remote Auto Start / Stop capability via two wire, closed contact logic, allows for connection to automatic transfer switchgear and other remote starting devices.
- Heavy-Duty steel skid base with anti-vibration isolators and start panel stand
- Lift bail assembly
- Radiator assembly with grill, fan and belt guards
- Exhaust muffler assembly (remote mount or engine mount)
- Air cleaner assembly
- Battery cables
- Operators manual and start instruction procedures
- Unit serviced and load tested

#### **DIMENSIONS:**

Length– 2108mm (83")  
 Width– 902mm (35.5")  
 Height– 1500mm (59")  
 Weight– 953kg (2100lbs)  
*\*Approx. dimensions*



## WQ60 Westquip Generator

### ENGINE SPECIFICATIONS:

- Isuzu 4JJ1X EPA Tier 3 liquid cooled diesel
- 101Hp @ 1800 RPM / 84HP @ 1500 RPM
- 12V electrics
- Electric and self priming fuel lift pump
- Turbo-charged and inter-cooled
- Fuel water separator filter
- 500-hour oil drain & service interval
- In-line 4 cylinder, 4 stroke
- Displacement: 3.0L
- Glow plug cold starting aid
- Electronic governor engine control
- Isuzu 5 year/5000-hour engine warranty
- Fan, belt, and core guards
- Primary and secondary fuel filters

### GENERATOR SPECIFICATIONS:

- Newage-Stamford
- Single bearing, brushless
- Automatic Voltage Regulator (AVR Controlled)
- +/- 1% voltage regulation
- Optional PMG available
- IP23 enclosure protection
- Class H insulation
- 1 year warranty
- UL/CSA approved

### OPTIONAL ACCESSORIES:

- Remote oil drain kit
- Oil level site glass/shutdown
- Engine coolant heater—120V
- Batteries and box
- Auto-start control panel
- Oilfield skid building and container installation packages
- Sub-base fuel tank
- Main circuit breaker
- A/C Distribution Electrical Panel
- Positive air safety shutoff valve
- Residential grade muffler
- Generator enclosure/housing with sub-base tank

### WARRANTY: all models are covered by a comprehensive limited warranty

- Package: 1 year / unlimited hours
- Isuzu Engine: 0-12 months / unlimited hours; 5 year / 5000-hour major component warranty
- Newage-Stamford Generator: 1 year / unlimited hours

