

## WQ8-ENCL Westquip Generator



### WQ8-ENCL Enclosed Diesel Generator

Continuous output 60Hz: 8kW  
Standby output 60Hz: 9kW

Continuous output 50Hz: 7kW  
Standby output 50Hz: 8kW

Fuel Consumption L/hr: 1/2 load: 1.6 Full load: 2.9

Generator set pictured may include optional accessories.

Voltage	Frequency	P.F.	Rating	Amps	kW	kVA
120/240 - 1PH	60Hz	1.0	Continuous	33	8	8
120/208 - 3PH	60Hz	0.8	Continuous	28	8	10
277/480 - 3PH	60Hz	0.8	Continuous	12	8	10
347/600 - 3PH	60Hz	0.8	Continuous	10	8	10

#### GENERATOR SET FEATURES:

- Isuzu liquid cooled diesel engine
- Newage-Stamford generator with Automatic Voltage Regulator -*CSA/UL approved*
- 12ga All-Weather powder coated metal enclosure. Hinged, lockable door access on both sides. Rear access door.
- Central lifting point
- Long Run 50 Imp. Gal (225L) internal fuel tank with fuel gauge– *141hr @ 1/2 load; 78hr @ full load!*
- Low oil pressure and high water temperature Safety Shutdown System
- Control panel with DC volt meter, hour meter, oil pressure and coolant temperature gauges with auto-start feature
- Heavy-Duty steel skid base with anti-vibration isolators
- G24 battery and box
- Operators manual and start instruction procedures
- Unit serviced and load tested

#### OPTIONAL Electrical Panel (120/240V 1 Phase)

40 Amp Circuit Breaker (Main)

#### Receptacles:

2 x 20 Amp Duplex

1 x 30 Amp 125/250V Twist lock





## WQ8-ENCL Westquip Generator

### TECHNICAL SPECIFICATIONS:

#### DIMENSIONS:

L x W x H (Skid): 72" x 32" x 52"

Weight Dry (Skid): 1635lb

Weight Wet (Skid): 2146lb

Fuel Tank Capacity: 60 Imp Gallons; 270L

L x W x H (Trailer): 129" x 60" x 72"

Weight Dry (Trailer): 2120lb

Weight Wet (Trailer): 2620lb

Run time: 169hr @ 50% load; 93hr @ 100% load

#### ENGINE SPECIFICATIONS:

- Isuzu 3CH1 EPA Tier 4 Final liquid cooled diesel
- 12.5HP @ 1500 RPM ; 15.0Hp @ 1800 RPM
- 12V electrics
- Electric and self priming fuel lift pump
- Naturally aspirated
- Fuel water separator filter
- In-line 3 cylinder, 4 stroke
- Displacement: 1.1L
- Cold start assist starting aid
- 3-5% mechanical governor engine control
- Isuzu 2 year/2000-hour engine warranty
- Fan, belt, and core guards

#### GENERATOR SPECIFICATIONS:

- Newage-Stamford
- Single bearing, brushless
- Automatic Voltage Regulator (AVR Controlled)
- +/- 1% voltage regulation
- IP23 enclosure protection
- Class H insulation
- 1 year warranty
- UL/CSA approved

#### TRAILER SPECIFICATIONS:

- Transport Canada approved
- 14" 205/75R14 Tires
- Front leveling jack
- Pintle eye coupler

#### OPTIONAL ACCESSORIES:

- Remote oil drain kit
- Sound attenuation
- Volt and Hertz AC meter gauges
- Positive air safety shutoff
- Engine coolant heater—120V
- Auto-start control panel



Optional: Large service access door (left)

Custom AC electrical Receptacles (right)

